

HCK-700T

Camera Control Keyboard



- ▶ Compact and ergonomics design with 4-axis joystick.
- ▶ Versatile applications of NDI cameras, video conference cameras, and IP cameras.
- ▶ High brightness OLED display for easy operation.
- ▶ 4-axis joystick for Pan / Tilt / Zoom and focusing.
- ▶ Supports RS-232 / RS-485 control for compatibility with most PTZ cameras.
- ▶ Key buttons for quick access to camera white balance, backlight compensation, and brightness.
- ▶ Supports the max. of 128 preset points.
- ▶ One unit allows controlling the max. of 255 cameras under different protocols.
- ▶ Auto backlight key for enhanced viewing and operation.
- ▶ Duplicate password protection from unauthorized operation and settings.

Specifications

Hardware Specs

Comm. Interface	RS232 / RS485
Protocol	VISCA / PELCO-D / PELCO-P
Baud Rate	2400 / 4800 / 9600 / 19200 / 38400 bps
Camera Address	1~255
Joystick	4-axis (Pan / Tilt / Zoom / Focus)
Display	OLED

Physical Properties

Dimensions (LWH)	200 x 120 x 103 (mm)
Net Weight	0.5 kg
Operating Temperature	0°C~+40°C
Storage Temperature	-20°C~+50°C
Relative Humidity	≤90% (non-condensed)

Power Supply

Power Source	DC12V±25%
Power Consumption	<2W