

H-32 | Wireless Handheld Microphone



Description

- Specially hardened aluminum housing provides light weight and high durability
- Detachable microphone capsule module design, can work with the latest version dynamic and condenser microphone capsule module of Relacart HR series, and the mic body is compatible with many mic capsule module with standard interface of Shure.
- The high-brightness OLED display can clearly display the working status of the microphone in any scene
- Hidden button design to prevent wrong operation during use
- An illuminated light touch switch on the tail with a mute function, when the microphone is in low battery, the light will turn red and flash to remind
- The gain and RF strength of the microphone can be adjusted according to the needs of the scene through the menu of the microphone

Product Specification

| | |
|--------------------------|--|
| Carrier Frequency Range: | 521.25MHz~936.85MHz |
| Harmonic Radiation : | <45dBm |
| Bandwidth : | 134MHz(depending on the region) |
| Modulation: | FM |
| Audio Compression: | Relacart classic audio compression circuit |
| Microphone Element: | Dynamic/Condenser(removable) |
| RF Output Power: | 100mW/50mW |
| Battery: | AA×2 |
| Current Consumption: | 175mA(Typical) |
| Battery Current/ Life: | Approximately 9 hours(alkaline) |
| Dimension(mm): | 53(Φ) ×275(L) |
| Weight: | Approximately 349g(w/o battery) |