MC2 | 2.4G DUAL-CHANNEL CAMERA MOUNT WIRELESS MICROPHONE SYSTEM



MC2 adopts 2.4GHz ISM global unlimited frequency band transmission to ensure high-quality audio output. It is suitable for video shooting, live streaming, recording, etc.
Whether you are a professional filmmaker or amateur, MC2 will be your effective assistant, helping you easily access high-quality audio content.

Key Features

Super Wide Frequency Range

- Adopt 2.4G ISM global unlimited frequency band transmission

Widely Compatible

- Widely compatible with computers, digital / SLR cameras, camcorders, voice recorders, tablets, and mobile phones.
- **USB-C/Lightning Connection for Mobile, Cameras and PC**

DSP digital audio companding

- 48KHz audio sampling rate to minimize noise in the systemwireless connection and providing high-fidelity audio output

Anti-Noise

- The product comes with a special microphone windproof furry to ensure clear sound pickup in outdoor or noisy environments

External Microphone Expansion

- In addition to the built-in microphone, the external microphone and line input function can also be used, and the receiver and transmitter can independently adjust the volumeaudio output

Magnetic Rubber Clip

- The innovative design of magnetic suction and soft glue, including a hot shoe magnet specially designed for the camera, makes the product easy to use, close to the collar during interviews or close to objects with iron, nickel and other metals, such as mobile phones, computers, etc., the novel design of magnetic rubber improves the flexibility of users in product application

Product Specification



MC2-R

Wireless Receiver

RF Carrier Frequency Range:	2400MHz~2483.5MHz
Modulation Type:	Frequency hopping/Digital FSK
Receiving Sensitivity:	-86dBm
Antenna Type:	Built-in PCB antenna
Display Mode:	OLED display
Power Supply Requirements:	Built in lithium battery, standard USB 5V charging via TYPE-C interface.
Battery Life:	≥ 6 hours
Output Interface:	3.5mm TRS, Type-C Digital output
Working Temperature:	-5℃~-+50℃
Max. Charging Current:	270mA/H
Charging Time:	≤ 2 hours
Dimensions (mm):	67 x 32 x 13.5
Weight:	26.8g



MC2-T

Wireless Transmitter

RF Carrier Frequency Range:	2400MHz~2483.5MHz
Modulation Type:	Frequency hopping/Digital FSK
Transmission Power:	10dBm
Antenna Type :	Built-in PCB antenna
Microphone Pickup Type:	Omnidirectional (built-in microphone)
Display:	OLED display
Power Supply Requirements:	Built-in lithium battery, standard USB 5V charging via TYPE-C interface.
Battery Life:	≥ 6 hours
Input Interface:	3.5mm TRS
Working Temperature:	-5℃ ~ +50℃
Max. Charging current:	270mA/H
Charging time:	≤ 2 hours
Dimensions (mm):	67 x 32 x 13.5
Weight:	27.4g